

Company Model	METTLER TOLEDO BBA226-(X)xxx	AWT 3275	AWT QC3265	AND HV-60KWP Multi Range	Ohaus Defender 7000	Doran 7400	RLW CW80	RLW CW90	Detecto EB-204	Gainco Duraweigh	WeightTech MicroWeigh
							*discont'd*				
Construction	Full SS base & column IP65/IP67 SS terminal Light washdown use	Full SS base, column, LC SS NEMA 4x/IP66 terminal	Full SS base, column, LC SS NEMA 4x/IP66 terminal	Titan Series IP65/NEMA4	Semi-Washdown IP66 ABS terminal SS base, column, LC	Full SS NEMA 4X & IP69K	Full SS	Full SS IP66 terminal SS base	Full SS	SS base; polymeric IP69k terminal	SS base/column ABS IP69k terminal
Approved Resolution	5,000d (15,000 max.)	6-100lb 3,000d, >100lb, 5,000d	6-100lb 3,000d, >100lb, 5,000d	3,000d	5,000d	5,000d	3,000d	5,000d	3,000d	3,000d	5,000d
Capacity Range lb	5 to 250	low: 6 to 100; med: 100 to 500	low: 6 to 100; med: 100 to 500	30 to 150	25 to 500	2 to 200		5 to 100	15 to 300	30,60,200	6 to 30 small"; (8x8,10x10) "bench";(14x14,16x16,18x18, 20x20)
Platform Sizes Available	9 (rectangular & square) potted aluminum or potted SS	low: 2; med: 2	low: 2; med: 2	13 x 16.5	6	3 (10x10,12x12,15x15)		2 (10x10, 12x12)	3 (10x12,14x16,24x20)	5 (8x8,10x10,12x12, 16x16,20x20)	
Load Cell	Potted SS	Potted SS, NEMA 4X/IP66	Potted SS w/shroud	IP65 w/Gortex membrane	IP67 SS	Potted aluminum	Potted SS	Potted aluminum		Potted SS	Potted SS
Load Cell cable length Units	lb, kg	10ft lb, oz, kg, g	10ft lb, oz, kg, g, lb/oz	6.5ft lb,kg	g,kg,oz,lb,lb-oz	lb,kg,g,oz,lb-oz		kg,gm,lb,oz,lb-oz	lb,kg,oz,g,lb-kg		lb,kg,g,oz
Display	7-segment 6-digit LED	Four color graphic wt display	7-segment 6-digit LCD or LED	7-segment VFD	LCD 3-color checkweigh LED	6 digit LED		14-segment 6 digit LED w/3-color over/under bar graph	7-segment 6 digit LCD	7-segment 6 digit LED	16 character LCD
Max. Excitation VDC	5	10	12		5			5			
Output Mv/V	2	2	2		3			-0.5 - 4.5			
Power	AC only	AC	AC; optional battery for LCD version	AC only	AC, 6 C-cell	AC; rechargeable batt. Is optional		AC	AC or battery	AC or optional Li-ON	AC or optional gel cell battery
Annunciators	(under,OK,over) or (count,pcs,apw),zero,net weigh range,lb,kg	tare,center zero,gross,net, over,under,accept,lb,kg,oz,g	over,under,accept,lb/kg/oz/g/lb-oz center zero	Hi/Lo/OK		lb,kg,g,oz,over,accept under,neg,zero,mot		%kg,gm,lb,oz, center of zero,G/B,N,T PT,neg,standstill	zero,gross,tare,net,low battery	gross,net,center of zero, motion,lb,kg,oz,g over,under,OK	gross,net,center of zero, motion
Other Specs	x10 readability RS232 6 overload stops modes for count, classify, checkweigh	optional RS232	LCD and LED versions optional RS232 or RS485	Triple range Counting 2yr warranty RS232 Std	RS232 Time/Date Counting Reversible rear housing	2yr warranty Quad-Spring overload system RS232 is standard		4 channels on CPU board ltd 2yr warranty two duplex serial ports	both bi-direct and output only RS232	5 piezo keys up to 8 I/O bi-direct RS232 IR port	5 piezo keys std IR, RS232/RS485 up to 6 I/O BlueTooth & Ethernet options
Approx List Price	\$1039	\$1775	\$1450	\$1255	\$1100	\$1280		\$1335	\$1200	\$1600	\$1550